
PROSOL 30-35-40


PUNCHED STAINLESS STEEL 1.4016
WITH PROTECTIVE FILM

PROSOL 30-35-40 in steel are punched joint - covers in stainless steel 1.4016 available in various widths. They are used to join floors of the same or differing material and thickness. The rounded shape also allows the profile to be used to edge shallow floors max. 5 mm thick. **PROSOL** is normally used to cover flaws and defects created during laying of ceramic/wood/parquet floors by covering the joint/threshold. **PROSOL** is recommended for all sorts of public environments: hotels, offices, shops and private dwellings; it guarantees an impeccable and attractive finish.


PLSAC 30F/308F/309F/308FS/309FS/3010FS/3016FS




PLSAC 35F/358F/359F/358FS/359FS/3516FS



PLSAC 40F/409FS




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS





STAINLESS ST. 1.4016 punched - with protective film
bar length **2,7 lm** - pack. **20 Pcs** - **54 lm** (**L 30 mm** - **108 lm**)

Article	Width-thick.		
PLSAC 30F	30 mm - 10/10		
PLSAC 35F	35 mm - 10/10		



1. Choose the suitable profile and cut it to the necessary length. **2.** Mark the position of the holes using the existing holes in the profile as reference. **3.** Insert the screw anchors into the drilled holes. **4.** Fix the profile using flathead screws suitable for the relative slots in the profile.



STAINLESS ST. 1.4016 punched with screws and screw anchors thermo packed - bar length **0,93 lm** - pack. **20 Pcs**

SELF PACK

Article	Width-thick.	
PLSAC 309FS	30 mm - 10/10	

COLOURS



AC - Polished stainless Steel 1.4016

PROSOL 30-35-40

PUNCHED POLISHED BRASS
WITH PROTECTIVE FILM

PROSOL 30-35-40 in brass are punched joint - covers in polished brass available in various widths. They are used to join floors of the same or differing material and thickness. The rounded shape also allows the profile to be used to edge shallow floors max. 5 mm thick. **PROSOL** is normally used to cover flaws and defects created during laying of ceramic/wood/parquet floors by covering the joint/threshold. **PROSOL** is recommended for all sorts of public environments: hotels, offices, shops and private dwellings; it guarantees an impeccable and attractive finish.


PLSOL 30F/308F/309F/3010F/3016F/308FS/309FS/3010FS/3016FS




PLSOL 35F/359F/358FS/359FS/3510FS/3516FS



PLSOL 40F/409F/409FS/4016FS




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS






POLISHED BRASS punched with protective film
bar length **2,7 lm** - pack. **40 Pcs** - **108 lm** (**L 35/40mm** - **54 lm**)

Article	Width-thick.		
PLSOL 30F	30 mm - 10/10		





COLOURS



OL - Polished brass

1. Choose the suitable profile and cut it to the necessary length. **2.** Mark the position of the holes using the existing holes in the profile as reference. **3.** Insert the screw anchors into the drilled holes. **4.** Fix the profile using flathead screws suitable for the relative slots in the profile.